



SAFE 4 C

Safe 4 C films are perfectly transparent and help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Comply with European Standard EN 12600.



SOLAR SCREEN® Warranty 10 YEARS



Fire-resistance rating M1



Storage from -5°C to +40°C





European Standard EN 12600 **2B2**



REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:

122 cm

152 cm

183 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| Ultraviolet transmission | 5 % |
|---|------------|
| Visible light transmission | 85 % |
| Reflection of external visible light | 11 % |
| Reflection of internal visible light | 11 % |
| Total solar energy rejected | 19 % |
| Total solar energy rejected 2* | 19 % |
| Solar ratio: | |
| Solar energy reflection | 9 % |
| Solar energy absorption | 14 % |
| Solar energy transmission | 77 % |
| Reduction in Solar Glare | 14 % |
| g-value | 0.83 |
| u-value | 5.7 |
| Shading coefficient | 0.9 |
| | |
| Tensile strength (kg/cm ²) | 28 |
| Tensile strength (kg/cm²) Elongation at break | |
| | 28 |
| Elongation at break | 28 |
| Elongation at break Installation type : Interior | 28 125% |

Colour from the outside:

TRANSPARENT

CONSTRUCTION

- Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
 High optical quality polyester
- 3. Reinforced PS adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
- 4. Protection release liner, disposable after installation


INSTALLATION ADVICE

Vertical installation and on standard glass surface**

| Clear single pane | V |
|--------------------------------|----------|
| Tinted single pane | ~ |
| Reflective tinted single pane | ~ |
| Clear double pane | ~ |
| Tinted double pane | V |
| Reflective tinted double pane | ~ |
| Gas-filled double pane - Low E | ~ |
| STADIP EXT. clear double pane | ~ |
| STADIP INT. clear double pane | V |
| | |

recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m2.



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.